



JCB 3DXL_{PLUS}







Higher output in front loading application



Digital Display, Auto Idle, Auto Stop, Trip Meter etc.



LiveLink 4.0 & Intellidignostic for Enhanced Uptime





To know more



Scan the QR code









JCB 444,CRDI, 55kW (74hp) @ 2200 rpm, 4 cylinder with EGR Diesel Engine.

TRANSMISSION

The JCB synchroshuttle transmission provides superb drive power in all conditions. It consists of a 4-speed, fully synchromesh, smooth shift gear box with integral torque convertor and electrically operated reversing shuttle.

HYDRAULIC PUMP FLOW

114 lpm at 2000 rpm.

HYDRAULIC PRESSURE

3915 p.s.i. (270 Bar) system

BRAKES

JCB 'Q' brakes, hydraulically actuated, dual line, self adjusting (compensated), oil immersed, multi-disc type on the rear axle, well protected from dirt, water etc. requiring no maintenance. Operated through independent pedals linked together for normal use

STEERING

Power track steering rod system provides equal turn steering & quick response with less operating force.

- Working pressure 2 320 p.s.i. (160 bar)
- ·Oil supply from steering pump passing through suction strainer & return line filter.

ELECTRICAL

130 Ampere-hour 12 Volts battery system with alternator and full road lighting.

TYRES

Front: 9 x 16 - 16 PR Rear : 16.9 x 28 - 12 PR

SHIPPING WEIGHT

7620 kg

WHEELBASE

2.17 (7-1)

SHOVEL SIZE

I.I (38.85) cu.m

DUMP HEIGHT

2.74 (8-12) m

LOAD OVER HEIGHT

3.32 (10-11) m

MAX REACH AT FULL HEIGHT

1.15 (3-9) m

LOADER ARM BREAKOUT FORCE

5635 kgf

EXCEEDING EXPECTATIONS EVERYWHERE



6000+ Trained service engineers















Track your machine at your fingertips, download from:







Call us for a demo: 1800-1037-386

Follow us: f 🔰 🔼 🔘 in /JCBIndiaLtd









